

Applicant : Tian,ong Liu et al.
Serial No. : 09/988,053
Filed : November 16, 2001
Page : 2 of 13

Attorney's Docket No.: 13854-052001

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

Listing of Claims:

1. (Currently Amended) An integrated optical time division multiplexing (OTDM) module comprising:

an integrated modulator chip for generating at least first and second optical Return-to-Zero signal streams; and

an integrated time-delay chip coupled to the integrated modulator chip for introducing a prescribed optical delay between said ~~the~~ at least first and second optical Return-to-Zero signal streams and for combining said ~~the~~ at least first and second optical Return-to-Zero signal streams after introduction of the prescribed delay, the integrated time-delay chip including a plurality of waveguides formed on a substrate of the integrated time-delay chip for introducing an optical delay and operable to guide the at least first and second optical Return-to-Zero signal streams through the integrated time-delay chip,

where the integrated time-delay chip is operable to combine the at least first and second optical Return-to-Zero signal streams including interleaving the plurality of waveguides on the integrated time-delay chip.

2. (Original) An integrated OTDM module according to claim 1 wherein the integrated modulator chip is a twin-modulator chip.

3. (Previously Presented) An integrated OTDM module according to claim 1 wherein the integrated time-delay chip introduces a fixed optical time delay between said first and second optical Return-to-Zero signal streams.

Applicant : Tiangong Liu et al.
Serial No. : 09/988,053
Filed : November 16, 2001
Page : 3 of 13

Attorney's Docket No.: 13854-052001

4. (Previously Presented) An integrated OTDM module according to claim 1 wherein the integrated time-delay chip introduces a tunable optical time delay between said first and second optical Return-to-Zero signal streams.
5. (Previously Presented) An integrated OTDM module according to claim 1 wherein the time-delay chip comprises first and second waveguides for receiving said first and second optical Return-to-Zero signal streams from said integrated modulator chip, one of said first and second waveguides being of greater length than other of said first and second waveguides and both first and second waveguides being integrated within the fixed delay chip.
6. (Original) An integrated OTDM module according to claim 5 wherein an electrode is deposited over a portion of said first or second waveguide of the time-delay chip that is greater in length, wherein a voltage applied to the electrode is used for fine tuning the optical time delay introduced by the time-delay chip.
7. (Original) An integrated OTDM module according to claim 1 wherein an epoxy is used to couple optically and mechanically the integrated modulator chip to the integrated time-delay chip.
8. (Original) An integrated OTDM module according to claim 1 wherein an optical refractive index matching layer is used to couple optically and mechanically the integrated modulator chip to the integrated time-delay chip.
9. (Original) An integrated OTDM module according to claim 7 wherein the epoxy has a refractive index n , the integrated modulator chip has a refractive index n_1 , the integrated time-delay chip has a refractive index n_2 and wherein the refractive index n of the epoxy is defined by $n_1 < n < n_2$.

Applicant : Tianqong Liu et al.
Serial No. : 09/988,053
Filed : November 16, 2001
Page : 4 of 13

Attorney's Docket No.: 13854-052001

10. (Original) An integrated OTDM module according to claim 8 wherein the optical refractive index matching layer has a refractive index n , the integrated modulator chip has a refractive index n_1 , the integrated time-delay chip has a refractive index n_2 and wherein the refractive index n of the optical refractive index matching layer is defined by $n_1 < n < n_2$.
11. (Original) An integrated OTDM module according to claim 1 wherein the integrated modulator chip has a refractive index n_1 and an optical mode field diameter OMFD1, the integrated time-delay chip has a refractive index n_2 and an optical mode field diameter OMFD2 and wherein the refractive index n_1 and optical mode field diameter OMFD1 of the integrated modulator chip is substantially similar to the refractive index n_2 and optical mode field diameter OMFD2 of the integrated time-delay chip.
12. (Original) An integrated OTDM module according to claim 1 wherein collimating lenses are used to couple the integrated modulator chip to the integrated time-delay chip.
13. (Currently Amended) An integrated OTDM module according to claim 1 wherein the prescribed optical delay introduced between said the first and second optical Return-to-Zero signal streams is approximately one half the period of each of the first and second optical Return-to-Zero signal streams.

Applicant : Tiangong Liu et al.
Serial No. : 09/938,053
Filed : November 16, 2001
Page : 5 of 13

Attorney's Docket No.: 13854-052001

14. (Currently Amended) An integrated optical time division multiplexing (OTDM) module comprising ~~an integrated modulator chip coupled to an integrated time-delay chip via an optical refractive index matching layer wherein:~~

the integrated modulator chip comprises an input fiber tube for receiving an end portion of an input fiber, first and second modulators each connected on input ends thereof to the input fiber tube and on output ends thereof to respective first and second variable optical attenuators, said first and second variable optical attenuators having respective first and second outputs coupled to an input end of said integrated time-delay chip; and

the integrated time-delay chip comprises first and second waveguides, formed on a substrate of the integrated time-delay chip and operable to guide the first and second optical Return-to-Zero signal streams through the integrated time-delay chip, for receiving said respective first and second outputs of said first and second variable optical attenuators of the integrated modulator chip, one of said first and second waveguides being of greater length than the other of said first and second waveguides, the integrated time-delay chip further comprising an output fiber tube for securing an end portion of an output fiber,

where the integrated time-delay chip is operable to combine the at least first and second optical Return-to-Zero signal streams including interleaving the plurality of waveguides on the integrated time-delay chip.

Applicant : Tian,ong Liu et al.
Serial No. : 09/948,053
Filed : November 16, 2001
Page : 6 of 13

Attorney's Docket No.: 13854-052001

15. (Currently Amended) An integrated optical time division multiplexing (OTDM) module comprising ~~an integrated modulator chip coupled to an integrated time-delay chip via collimating lenses wherein:~~

the integrated modulator chip comprises an input fiber tube for receiving an end portion of an input fiber, first and second modulators each connected on input ends thereof to the input fiber tube and on output ends thereof to respective first and second variable optical attenuators, said first and second variable optical attenuators having respective first and second outputs coupled to an input end of said integrated time-delay chip; and

the integrated time-delay chip comprises first and second waveguides, formed on a substrate of the integrated time-delay chip and operable to guide the first and second optical Return-to-Zero signal streams through the integrated time-delay chip, for receiving said respective first and second outputs of said first and second variable optical attenuators of the integrated modulator chip, one of said first and second waveguides being of greater length than the other of said first and second waveguides, the integrated time-delay chip further comprising an output fiber tube for securing an end portion of an output fiber.

Applicant : Tianrong Liu et al.
Serial No. : 09/988,053
Filed : November 16, 2001
Page : 7 of 13

Attorney's Docket No.: 13854-052001

16. (Currently Amended) An integrated optical time division multiplexing (OTDM) module comprising an integrated time-delay chip coupled to an integrated modulator chip via collimating lenses wherein:

the integrated time-delay chip comprises an input fiber tube for receiving an end portion of an input fiber carrying an input optical signal stream, the integrated time-delay chip further comprising first and second waveguides, formed on a substrate of the integrated time-delay chip, each waveguide carrying an optical signal stream derived from ~~said the~~ input optical signal stream and wherein one of said first and second waveguides is greater in length than the other of said first and second waveguides for providing a delay between the first and second optical signal streams, ~~said the~~ first and second waveguides used for delivering the ~~said~~ optical signal streams to the integrated modulator chip; and

the integrated modulator chip comprises first and second waveguides for receiving the ~~said~~ optical signal streams from the ~~said~~ integrated time-delay chip, the integrated modulator chip further comprising first and second variable optical attenuators each connected on output ends thereof to respective first and second modulators and wherein an end facet of the integrated modulator chip is coated with a highly reflective coating.

Applicant : Tianqiong Liu et al.
Serial No. : 09/988,053
Filed : November 16, 2001
Page : 8 of 13

Attorney's Docket No.: 13854-052001

17. (Currently Amended) An integrated optical time division multiplexing (OTDM) module comprising:

an integrated time-delay chip adapted to receive an incoming short-pulse signal stream from a pulsed source, said the integrated time-delay chip comprising first and second waveguides formed on a substrate of the integrated time-delay chip for guiding the signal streams through the integrated-time delay chip and adapted to divide the incoming short-pulse signal stream into first and second short-pulse signal streams for transmission along said the first and second waveguides of said integrated time-delay chip, one of said the first and second waveguides being of greater length than other of said the first and second waveguides thereby introducing a prescribed optical delay between said the first and second short-pulse signal streams; and

an integrated modulator chip coupled to said the integrated time-delay chip, said the integrated modulator chip comprising first and second waveguides and adapted to receive said the first and second short-pulse signal streams from the integrated time-delay chip and to generate first and second optical Return-to-Zero signal streams from said the first and second short-pulse signal streams, wherein an end facet of said the integrated modulator chip is coated with a reflective coating to reflect said the first and second optical Return-to-Zero signal streams along said the first and second waveguides of the integrated modulator chip towards said the first and second waveguides of the integrated time-delay chip.

Applicant : Tiangong Liu et al
Serial No. : 09/988,053
Filed : November 16, 2001
Page : 9 of 13

Attorney's Docket No.: 13854-052001

18. (Currently Amended) An integrated optical time division multiplexing (OTDM) module comprising:

an integrated modulator chip for generating a plurality of optical Return-to-Zero signal streams; and

an integrated time-delay chip coupled to the integrated modulator chip for introducing prescribed optical time delays between each of the said plurality of optical Return-to-Zero signal streams and for combining said plurality of optical Return-to-Zero signal streams after introduction of said the prescribed delays, the integrated time-delay chip including a plurality of waveguides formed on a substrate of the integrated time-delay chip for introducing an optical delay and operable to guide the plurality of optical Return-to-Zero signal streams through the integrated time-delay chip,

where the integrated time-delay chip is operable to combine the at least first and second optical Return-to-Zero signal streams including interleaving the plurality of waveguides on the integrated time-delay chip.

19. (New) The integrated optical time division multiplexing (OTDM) module of claim 14, further comprising an integrated modulator chip coupled to an integrated time-delay chip via an optical refractive index matching layer.

20. (New) The integrated optical time division multiplexing (OTDM) module of claim 15, further comprising an integrated modulator chip coupled to an integrated time-delay chip via collimating lenses.